Product Technical Sheet

03 feb 2023 21:50



313.1647

PROLONGADOR

16A 3P+N+T 6h 346-415V 50Hz 60Hz Bornes con tornillo

Product Approvals

TECHDATA	
Tipo de producto	PROLONGADOR
Serie comercial	Serie OPTIMA
Descripción	PROLONGADOR
Tipo de instalación	PORTÁTIL
Intensidad nominal	16A
Polos	3P+N+T
Posición de hora	6h
Tensión nominal (range)	250-400V
Tensión nominal	346-415V
Frecuencia nominal	60Hz
Frecuencia nominal	50Hz
Color	ROJO
Material	TERMOPLÁSTICO
Grado de protección	Splash proof
Grado de protección IP	IP44/IP54
Grado de protección IK	IK08
Tipos de salidas disponibles	RECTA
Bornes	Bornes con tornillo

STANDARDS AND LAWS	
EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive

Material de los contactos	CuZn (latón)
Salida del cable	PRENSAESTOPA