

# 16D33-UE

Female Plug, 2/0 - 4/0 AWG, Double Set Screw Termination

16 Series Taper Nose Cam-Type Female Plug, Contact & Insulator, Detachable, Double Set Screw Termination, 2/0 - 4/0 AWG, 400 Amp Max, Type 3R When Mated, Black

- Single or double set screw or crimp tube termination
- NEMA 3R rated for outdoor use when mated
- Designed with cylindrical profile to reduce snap
- UL: 1691, 508 35k A / 600V Short Circuit Current Rating
- Color-coding provides fast and easy phase identification
- Common applications: entertainment, oil and gas, mining operations, power distribution, construction sites, and other temporary power applications

### **Technical Information**

**Electrical Specifications** Max. Amperage: 400 Amp Max. Voltage: 600 Volt

Material Specifications Contacts: Brass

Strain Relief: Copper Wire Mechanical Specifications Cable Range: 2/0 - 4/0 AWG Connection Type: Double Set Screw

Gender: Female

Standards and Certifications NEMA Rating: Type 3R

**UL**: 1691, 508 – 35k A / 600V Short Circuit Current Rating

**Product Features** Color: Black





**UPC Code:** 078477715895 Country Of Origin: Mexico

## Available Colors :



# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

# Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920  $\cdot$  FAX: +1-800-832-9538  $\cdot$  Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

#### Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

## Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

