Product Technical Sheet

03 feb 2023 22:15



313.1643H

PROLONGADOR

16A 2P+T 6h 200-250V 50Hz 60Hz Bornes con tornillo Con el dispositivo SAFE-IN

Product Approvals

TECHDATA	
Serie comercial	Serie OPTIMA
Tipo de producto	PROLONGADOR
Descripción	PROLONGADOR
Tipo de instalación	PORTÁTIL
Intensidad nominal	16A
Polos	2P+T
Posición de hora	6h
Tensión nominal (range)	200-250V
Tensión nominal	200-250V
Frecuencia nominal	60Hz
Frecuencia nominal	50Hz
Color	AZUL
Material	TERMOPLÁSTICO
Grado de protección	Splash proof
Grado de protección IP	IP44/IP54
Grado de protección IK	IK08
Tipos de salidas disponibles	RECTA
Bornes	Bornes con tornillo

STANDARDS AND LAWS	
EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive

Material de los contactos	CuZn (latón)
Salida del cable	PRENSAESTOPA
Opciones	Con el dispositivo SAFE-IN