


Especificaciones técnicas:


Curvas Conduit KRALOY

CURVA 90 ° H/H




Diámetro (Pulgadas)	A (in)	B (in)	C (in)
½	0.840	1.500	4.00
¾	1.050	1.500	4.500
1	1.315	1.875	5.750
1¼	1.660	2.000	7.250
1½	1.900	2.000	8.250
2	2.375	2.000	9.500
2½	2.875	3.000	10.500
3	3.500	3.125	13.000
4	4.500	3.375	16.000
6	6.625	3.750	30.000

CURVA 45 ° H/H



Diámetro (Pulgadas)	A (in)	B (in)	C (in)
½	0.840	1.500	4.000
¾	1.050	1.500	4.500
1	1.315	1.875	5.750
1¼	1.660	2.000	7.250
1½	1.900	2.000	8.250
2	2.375	2.000	9.500
2½	2.875	3.000	10.500
3	3.500	3.125	13.000
4	4.500	3.375	16.000
6	6.625	3.750	30.000

CURVA 30 ° H/H



Diámetro (Pulgadas)	A (in)	B (in)	C (in)
½	0.840	1.500	4.000
¾	1.050	1.500	4.500
1	1.315	1.875	5.750
1¼	1.660	2.000	7.250
1½	1.900	2.000	8.250
2	2.375	2.000	9.500
2½	2.750	3.000	10.500
3	3.500	3.125	13.000
4	4.500	3.375	16.000
6	6.625	3.750	30.000